

BAUM

Pneumatics Inc.

Specifications

A-3350

Model H9 Diverter Valve
2 - Way Hand Wheel

Rev. 0

03 / 03

| LINE SIZE | 6 $\frac{5}{8}$ | 8 $\frac{5}{8}$ | 10 $\frac{3}{4}$ | 12 $\frac{3}{4}$ | 14 | 16 | 18 | 20 | 22 | 24 |
|-----------|------------------|------------------|-------------------|--------------------|--------------------|--------------------|--------------------|-------------------|-------------------|-------------------|
| A | 86 $\frac{3}{8}$ | 86 $\frac{3}{8}$ | 110 | 130 $\frac{1}{4}$ | 130 $\frac{1}{4}$ | 168 $\frac{3}{4}$ | 168 $\frac{3}{4}$ | 191 $\frac{3}{4}$ | 191 $\frac{3}{4}$ | 211 $\frac{1}{4}$ |
| B | 76 $\frac{1}{8}$ | 76 $\frac{1}{8}$ | 94 $\frac{7}{16}$ | 112 $\frac{5}{16}$ | 112 $\frac{5}{16}$ | 148 $\frac{3}{16}$ | 148 $\frac{3}{16}$ | 166 $\frac{1}{4}$ | 166 $\frac{1}{4}$ | 184 $\frac{1}{4}$ |
| C | 13 $\frac{1}{4}$ | 13 $\frac{1}{4}$ | 16 $\frac{3}{8}$ | 19 $\frac{3}{8}$ | 19 $\frac{3}{8}$ | 25 $\frac{5}{8}$ | 25 $\frac{5}{8}$ | 28 $\frac{3}{4}$ | 28 $\frac{3}{4}$ | 32 |
| D | 11 $\frac{3}{4}$ | 13 | 16 $\frac{1}{4}$ | 18 $\frac{1}{4}$ | 18 $\frac{1}{4}$ | 21 $\frac{3}{4}$ | 22 $\frac{3}{4}$ | 25 $\frac{3}{4}$ | 26 $\frac{3}{4}$ | 29 $\frac{3}{4}$ |
| E | 1 $\frac{1}{8}$ | 1 $\frac{1}{8}$ | 1 $\frac{5}{8}$ | 1 $\frac{5}{8}$ | 1 $\frac{5}{8}$ | 2 $\frac{1}{4}$ | 2 $\frac{1}{4}$ | 2 $\frac{1}{2}$ | 2 $\frac{1}{2}$ | 2 $\frac{3}{4}$ |
| WT. | 410 | 550 | 750 | 1100 | 1200 | 1700 | 2300 | 2600 | 2800 | 3500 |

NOTE: Dimensions in inches, weight in lbs, varying slightly with production models.
Request certified drawings of particular models or applications for exact dimensions.

NOTES :

1. VALVE MUST BE MOUNTED ON A RIGID STRUCTURE OR CONCRETE FOUNDATION.
2. THE PIVOT MAY BE ROTATED 360° IN INCREMENTS OF 90° TO COMPENSATE FOR UNEVEN WEAR OR THE TAPER.
3. VALVE MAY BE MOUNTED HORIZONTALLY, SLOPED VERTICALLY, OR SIDEWAYS.
4. SUPPORT PIPES INDEPENDENTLY OF VALVE
5. RIGHT HAND OFFSET SHOWN (LOOKING IN DIRECTION OF FLOW)

H9

HandWheel

