



WWW.BAUMPNEUMATICS.CA

Specifications

Universal Blower Base (Multi Base) Model 14-H Exploded View

A-7862

Rev. 1

04 / 18

PARTS LIST

ITEM	QTY	PART NUMBER	DESCRIPTION	MATERIAL
1	1	1435-RBST8	REBUILT P.D. BLOWER, 4300 LB	1435-HOLMES
2	1	A8000-16	INTAKE SCREEN W/ PACK	STEEL
3	4		H1435, GASKET FULL FACE	NEOPRENE
4	2	1616-H1435	16" 1435-H X 1/2 VIBRATION FLANGE	STEEL
5	1	A8100-16	SILENCER 1616	STEEL
6	1	ECP84407T-5	200HP, 1785RPM, 3PH, 60HZ, 447T, A44120M, 575 V	200HP BALDOR
7	1	447TB2	MOTOR SLIDE BASE 447T, DBL ADJUSTER	STEEL
8	1	A7860-UBB14-H	BASE SUPPORT FRAME	STEEL
9	1	14MX67S-68	DRIVER PULLY (MOTOR), 11.75	GATES*
10	1	3225 X 3.375	TAPERLOCK BUSH DRIVER	STEEL
11	1	14MX168S-68	DRIVEN PULLY (BLOWER) 29.4	STEEL
12	1	4535 X 3.75	TAPERLOCK BUSH DRIVEN	STEEL
13	1		UBB14-H-GB	STEEL
14	1	14MGT392068	BELT POLYCHAIN GATES GT2	POLYCHAIN
15	4		HHCS 3/4 - 10 UNC X 3 1/2 W/ F /WASH PLATED	STEEL
16	8		HHCS 7/8 - 9 UNC- X 3 1/2 W/ F /WASH PLATED	STEEL
17	4		HHCS 3/4 -10 UNC X 2 W/ F /WASH PLATED	STEEL
18	2	A9269-12	VIB CLAMP 12X6 TYPE1	ST/ST
19	1	A9269-16	VIB CLAMP 16X6 TYPE2	ST/ST
20	1		TAPER. FAB	STEEL
21	1	A9650	SIMPLE CONTROL PANEL,(A9652 WIRING SCHEMATIC)	STEEL
22	1		NAME PLATE "BAUM"	STEEL
23	1		PIPE, 12 DIA, 6 1/2 LONG	STEEL

- 7 STANDARD NEMA MOTOR SIZES (50-200 HP)
- EASY INSTALLATION WITH JACKING SCREWS AND BUILT-IN FORK LIFT POCKETS
- DESIGNED FOR BOLT-IN EXCHANGE OF THE FOLLOWING BLOWERS W/O FIELD CUTTING OR WELDING:

1033 HOLMES
1232 HOLMES
1435 HOLMES

*- GATES, OR
- CONT,
- MARTIN

